STI BEAM SMOKE DAMAGE STOPPER®





STI-9706

PRODUCT OVERVIEW

Five models are offered to protect the vital sensor units of projected beam type smoke detectors in large areas (such as gymnasiums, warehouses and auditoriums). STI Beam Smoke Damage Stoppers are designed to protect both transmitter and receiver sensors. Installation is simple with anchors and screws provided.

BACKED BY A THREE YEAR GUARANTEE

As all STI protective covers, Beam Smoke Damage Stoppers are backed by a three year guarantee against breakage in normal use. They are constructed of 9-gauge, welded steel wire coated with a tough, corrosion resistant polyester shell.

KEY FEATURES General Information

- Protection against misalignment and false fire alarms.
- Three year guarantee against breakage in normal use.

Design

• Designed to protect both transmitter and receiver units (sold individually).

Construction

- Super tough construction of 9-gauge coated steel wire makes guards extremely difficult to break.
- · Coated with a tough, corrosion resistant polyester shell.

Installation

- · Fast and easy installation.
- May be painted once prior to installation.

Options

· Five sizes available.



Safety Technology International

STI Beam Smoke Damage Stopper®


Dimensions and Technical Information

MODELS AVAILABLE

STI-9623	Beam Smoke Damage Stopper for DS240 & DS241
STI-9624	Beam Smoke Damage Stopper for Fireray 50/100 R
STI-9625	Beam Smoke Damage Stopper for System Sensor
	Beam Smoke Detector 6424
STI-9706	Beam Smoke Damage Stopper - flush mount for
	System Sensor 1224
STI-9707	Beam Smoke Damage Stopper - surface mount
KIT-82	Tamper resistant stainless steel screws, #8 x 1 1/2
	in. snake eye
KIT-19038	5/16 in. hex drive tamper bit for tamper resistant
	screws

MODEL	HEIGHT	WIDTH	DEPTH
STI-9623	7.75 in. (196mm)		6 in. (152mm)
STI-9624	8.875 in. (225mm)	5.5 in. (140mm)	4.75 in. (120mm)
STI-9625	7.875 in. (200mm)	10.25 in. (260mm)	12.625 in. (321mm)
<u>STI-9706</u>	10.82 in. (275mm)	9.32 in. (237mm)	4 in. (120mm)
STI-9707	11 in. (280mm)	9.62 in. (244mm)	5.5 in. (140mm)


NOTE: No tamper resistant stainless steel screws available for STI-9625.




STI-9624

4.75 in. (120mm)

> 8.875 in. (225mm)






APPROVALS AND WARRANTY

TESTING


STI-9625 has been tested and approved or listed by: · UL, cUL Listed S3504 for use with System Sensor beam detector model 6424.


WARRANTY

Three year guarantee against breakage in normal use.



6	Π			Π		
		\int	¥	N		
				1		
		CEN	İTEI	R	1	
	H	* CU1	0 U	T	Ħ	
	Ц			1	Н	
		\	<u> </u>			
	П		П			L





STI-9706

STI-9707

Safety Technology International

2306 Airport Road Waterford, Michigan 48327, USA

Tel: 248-673-9898 Fax: 248-673-1246 Toll-free: 800-888-4784 info@sti-usa.com www.sti-usa.com

Taylor House 34 Sherwood Road Bromsgrove, Worcestershire B60 3DR, England

Tel: +44 (0)1527 520 999 Fax: +44 (0)1527 501 999 info@sti-emea.com www.sti-emea.com