

LIMITED LIABILITY WARRANTY

Your new Camera is guaranteed to be free from defects in materials and workmanship for a period of two years from the date of purchase.

The product must have been used only for its intended purpose, and not been subjected to damage by misuse, willful or accidental damage, caused by excessive voltage or lightning.

The product must not have been tampered with in any way then the guarantee will be considered null and void.

This guarantee does not affect your statutory rights.

Contact VITEK directly for all servicing.



28492 CONSTELLATION ROAD VALENCIA, CA 91355
WWW.VITEKCCTV.COM | 888-VITEK-70



VT-IR124/24 124 LED IR Illuminator with 100 Foot Range



- 124 IR LEDs for over 100' Illumination Range
- Weather Resistant Aluminum Construction for Outdoor Use in Most Environments
- Attractive and Compact styling (Approximately 4" in Diameter)
- CDS Sensor Turns Unit On at Night Automatically
- 24 Volt AC Operation



CAUTION
RISK OF ELECTRICAL SHOCK
DO NOT OPEN



1. Unit contains uninsulated dangerous voltage within the enclosure that may be of sufficient magnitude to constitute a risk of electric shock to persons
 2. Only use AC Power Supply
 3. Read & Keep these instructions.
 4. Heed to all warnings and follow all instructions carefully.
 5. Do not use near water.
 6. Clean only with dry cloth.
 7. Do not block any ventilation openings. install in accordance with the instructions.
 8. Do not install near any heat source such as radiators, heat resisters, stoves, or other apparatus (including amplifiers) that produce heat.
 9. Do not defeat the safety purpose of the polarized or grounding-type plug. A polarized plug has to blades with one wider the other. A grounding type plug has to blades and a third grounding plug. The wide blade or the third prong are provided for safety. if the provided plug dose not fit into your into your outlet, consult an electrician for replacement of the obsolete outlet.
 10. Protect the power cord from being walked on a pinched particularly at plugs, convenience receptacle, and the point where they exit from the apparatus.
 11. Only use attachment/accessories specified by VITEK.
 12. Use only with cart, stand, tripod, bracket, or table specified by the manufacturer, or sold with the Unit,
 13. Unplug this unit during lightning storms or when unused for long periods of time.
 14. Refer all servicing to qualified service personnel, Servicing is required when the unit has been damaged in any way, such as power-supply cord or plug is damaged, liquid has been spilled or objects have fallen into the unit, the unit has been exposed to rain or moisture, does not operate normally or has been dropped.
 15. Do not attempt to service this product yourself as opening or removing covers may expose you to dangerous voltage or other hazards. Refer all servicing to qualified service personal.
- CAUTION** - To reduce the risk of electric shock, do not perform any servicing other than contained in these operating instructions unless you are qualified to do so.

SPECIFICATIONS

VT-IR124/24

Number of LEDs	124
Wave Length	850nm
Beam Spread	30°
Range	100 Feet
Power On	Automatic CDS Control
LED Lifetime	20,000 Hours
Construction	Aluminum
Weather Resistant	Yes
Operating Temperature	14°~122° (-20°C~50°C)
Power Source	AC 24V
Power Consumption	2A
Weight	1038 g. / 36.6 oz. / 2.29 lbs.
Dimensions (W x H x D)	3.94" x 5.39" x 6.38" (100 x 137 x 162mm)

